

Product data sheet

LED helmet lamp KS 7630-MCII uvex pheos



Product characteristics:

- LED head lamp with two switching levels
- Illuminance: 10000 Lux (distance light at 1m)
- Operating temperature: -20 °C to +50 °C
- Protection class IP 67
- Power source: Lithium battery 3,7 V - 3,4 Ah
- Charging time: < 9 hours
- Light duration: min. 6h to max. 30h
- Life expectancy accumulator: > 80% capacity after 500 charging cycles
- very low weight: 145g (incl. battery)
- ATEX approval (RiLi 2014/34/EU)

Technical data:

Protection class:	IP 67
Power source:	Lithium battery 3,7 V - 3,4 Ah
Luminous flux:	230 lm
Weight:	145g (incl. battery)

Use and storage:

Operating temperature:	-20 °C to +50 °C
Illuminance:	10000 Lux (distance light at 1m)
Light duration:	min. 6h (strong light), min. 30h (emergency light)
Illumination range:	Emergency light up to 80 m , Working light up to 140 m, strong light up to 190 m

Variants/colors:

Article-Nr.	Designation	Packaging unit
9790028	LED helmet lamp KS 7630-MCII uvex pheos	1 piece

UVEX ARBEITSSCHUTZ GMBH
Wuerzburger Str. 181-189
90766 Fuerth, GERMANY
T: +49 (0) 911 97 36 0
E: serviceteam@uvex.de
I: uvex-safety.de