

Product data sheet

uvex pheos LED Lights

**Product characteristics:**

- LED head lamp with two separate reflectors for distance and area light
- compact design, very low weight, extremely robust
- Four different operating modes

Technical data:

Protection class:	IP 67
Illuminance:	max. 6500 Lux
Light duration:	min. 5,5h (modes: high), min. 11h (modes: low)
Illumination range:	Area light 5-10 m, distance light 50-100 m
Luminous flux:	max. 115 lm
Power source:	Lithium battery 3,7 V - 1,7 Ah
Charging time:	< 4,5 hours
Accumulator life expectancy:	>80% capacity after 500 charging cycles
Weight:	86g
ATEX certification :	II 2G Ex ib IIC T4 (9790063/ 9790172)

Use and storage:

Operating temperature:	-20 °C to +50 °C
------------------------	------------------

Charging adapter

9790062; 9790063	9790172
Charging adapter type F	Charging adapter type E
	

Variants/colors:

Article-Nr.	Designation	Packaging unit
9790062	uvex LED head lamp pheos LED Lights	1 piece
9790063	uvex LED head lamp pheos LED Lights EX	1 piece
9790172	uvex LED head lamp pheos LED Lights EX type E	1 piece

UVEX ARBEITSSCHUTZ GMBH
Wuerzburger Str. 181-189
90766 Fuerth, GERMANY
T: +49 (0) 911 97 36 0
E: serviceteam@uvex.de
I: uvex-safety.de